### I-I. Leg Strength Test

#### Test Method:


Vertically apply a static load at I" from the end of the leg for I min. Force is applied in four directions (forward, rearward, side to side).

### Test loads are depended on different category of sample.

Table in Height	Table Top Area (sq.ft)		F-14 T-15-
	>5 sq.ft	≤ 5 sq.ft	Fording Table
>610mm	0.5 x (unit weight of sample, lb) + 50lb	0.5 x (unit weight of sample, lb) + 10lb	40lb
≤610mm	0.5 x (unit weight of sample, lb) + 10lb		40lb

#### Note:

- Maximum applied load is 75 lbs.
- · No part of leg should be touching the platform.



### Requirement:


No structural failure after leg strength test.


## I-2. Stability Test

### Test Method:

Test load is applied 1 in. from the edge of 12 in. disc.

Toma of Table	Table Top Area (sq.ft)		C1 - T-
Type of Table	≥ 4 sq.ft	< 4 sq.ft	Glass Top
Dinette Table	1001	901b	100lb
Card Table	100lb		
Computer Desk	125lb	N/A	
Coffee Table	75lb	651b	50lb
End Table	501b	40lb	50lb





### Requirement:


The table may not have any one leg lift off the floor or tipped over when test load applied.


## I-3. Concentrated Load Capacity Test

#### Test Method:

Test load is applied on 12 in. disc 6 in. from edge. Test load based on sq.ft. Not to exceed 300lb. Test load to be left for one hour.

Trung of Table	Table Top Area (sq.ft)		(T) T
Type of Table	≥ 4 sq.ft	< 4 sq.ft	Glass Top
Dinette Table			
Card Table	300lb	275lb	100lb
Computer Desk			
Coffee Table	2001ь	175lb	50lb
End Table	50lb	25lb	50lb





Example

### Requirement:


No structural failure or max. 1/2 in. deformation after loading test.

# I-4. Distributed Load Capacity Test

### Test Method:

Test load is applied evenly distributed on the surface. Test load based on sq.ft. Not to exceed 200lb. Test load to be left for one hour.

Type of Table	Table Top Area (sq.ft)		Glass Top
Type of Table	≥ 4 sq.ft	< 4 sq.ft	Glass 1 op
Dinette Table		40lb/sq.ft	100Ib
Card Table	50lb/sq.ft		
Computer Desk			
Coffee Table	40lb/sq.ft	30lb/sq.ft	50lb
End Table	20lb/sq.ft	10lb/sq.ft	50lb
Secondary Surface	≤16 inch depth (3lb x shelf width)		N/A
	>16 inch depth (5lb x shelf width)		N/A






Example

## I-5. Product Drop Impact Test

#### Test Method:

One end of table is dropped from a height of 10 in. and allowed to free fall to the test floor.





Example